EGHOLM

Rotary/mulch mower 1000

- Park Ranger 2155





1987 mm

Standard equipment:

Tilting for cleaning The mower

The mower can tilt up and rest on two support wheels making cleaning easy.

Stepless height adjustment

Cutting height can be infinitely adjusted via handle on

tne mower

Piano wheels Piano wheels which move the cutter in line with the manoeuvring are equipped with heavy slide bearings in

their wheel forks for durability.

Extra equipment (options):

Large radiator cover

To avoid choking of the radiator grill while mowing dry grass in dusty surroundings, the large radiator cover can be fitted. Can not be used in connection with a grass collector.

Mulch mower kit

The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.

Collection mower (kit)

Rebuild the rotary mover to a collection mower. Collecting the grass trimmings ensures the most professional looking result and healthiest lawn. It is recommended to use the dedicated grass collector for this purpose. Please see separate data sheet for this attachment.

Technical specifications

Length	mm	2800
Width	mm	1100
Height with / without cabin	mm	1987 / 1350
Storage dimensions		
Length	mm	880
Width	mm	1100
Height	mm	480
Weight		
Weight (rotary mower)	kg	90
Performance		
Ground clearance below mower	mm	80
No. of mower blades	pcs.	2
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1050
Adjustable cutting height	mm	30-70
Theoretical mowing area - rotary	m²/h	10500
Theoretical mowing area - mulch	m²/h	10500
Theoretical mowing area - collection	m²/h	8400
Max. recommended operating speed		
Rotary mower *	km/h	10
Mulch mower (shorter grass) *	km/h	10
Collection mower *	km/h	8
Noise emissions		
Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	99

^{*} Depends on grass and height.



